

L 330 S · L 331 S

One for all.  
All in one.

The L 330 S and L 331 S outdoor SensorLights bring pleasant, even lighting to your outside wall. Sleek, minimalist design makes it particularly suitable for driveways, garages or stairwells and round glass shade distributes light for illumination that's full of atmosphere. Incidentally, we have given these lights the very latest control system that's even capable of synchronizing several lights. The settings on the product are easy to understand. This way, one light controls the others at the same time.



- max. 60W
- E27
- infrared sensor 360°
- max. 8 m
- IP 44
- 2–2000 lux
- 5 sec–15 min
- networkable
- 1.8–2 m
- energy saving
- 3 JAHRE functional warranty

EAN L 330 S white	4007841 670115
EAN L 330 S silver	4007841 670214
EAN L 331 S white	4007841 670313
EAN L 331 S silver	4007841 670412
Dimensions (h x w x d)	275 x 255 x 110 mm
Power supply	230 - 240V/50Hz
Sensor type	passive infrared
Max. output	60 W / E 27
Additional switching capacity (resistive load, e.g. incandescent lamps)	300 W max.
in parallel mode	5 lights max.
Angle of coverage	360° with sneak-by guard
Capability of masking out individual segments	yes
Reach	8 m max. all-round
Response brightness	2 - 2,000 lx
Time setting	5 sec. - 15 min.
Permanent light 'ON'	selectable, all night or half the night
IP rating	IP44
Protection class	II
Material	UV-resistant plastic
Complete with lamp	no



L 330 S  
white




L 330 S  
silver



L 331 S  
white



L 331 S  
silver



Sensor with 3 intelligent programs



UV-resistant plastic

