

MD/PD IR 4360

Simply inspiring - the new motion and presence detectors from STEINEL

- Motion and presence detectors with Ø 8 m and Ø 24 m range
- Surface-mounted, recessed & flush-mounted versions
- Push-button input for manual override
- Adjustment via Smart Remote remote control or potentiometer
- Parallel connection of several sensors for range extension



4360-8



4360-24

 professional line



The sensors are easily adjusted with the Smart Remote or by potentiometer



Infrared sensors with 360° detection



Reach versions with Ø 8 m and Ø 24 m



Mounting height up to 4 m

Motion and presence detectors

MD/PD IR 4360



Motion detector (MD)

- Motion detection and light measurement
- Fully and semi-automatic mode
- Push-button input

Motion detector with COM1 interface

Presence detector (PD)

- Motion, presence detection and light measurement
- Presence detection function
- Fully and semi-automatic mode
- Push-button input (COM1)
- Black and white housing colour



Presence detector with COM1, KNX and DALI-2 IPD interface

Technical data

Mounting height max. 4,00 m
 Motion (MD+PD)..... Ø 8 m / Ø 24 m
 Presence (PD) Ø 2,5 m / Ø 4 m
 Dim. Flush-mounted Ø 109 x 70 mm
 Dim. Surface-mounted..... Ø 129 x 65 mm
 Dim. Ceiling installation..... Ø 109 x 138 mm

COM1 (ON/OFF)

Power 220-240V, 50/60Hz
 Relay switching loads 2000W, LED 500W
 Push-button input, fully/semi-automatic.....
 Parallel connection
 for range extension.....max. 10 sensors


DALI-2 IPD

Power Dali Bus
 Current consumption in mA 84 mA
 supplied data Movement, lux value


KNX

Current consumption in mA 10 mA
 KNX application 1 channel,
Constant light control, HVAC control,
 Presence object for
master/slave switching, 2 logic gates


3 designs



Flush-mounted



Surface-mounted



Ceiling installation

MD IR 4360-8 (Motion detector, Ø 8 m)

COM1

Flush-mounted, white 4007841 086893
 Surface-mounted, white..... 4007841 086909
 Ceiling installation, white 4007841 086886

MD IR 4360-24 (Motion detector, Ø 24 m)

COM1

Flush-mounted, white 4007841 086923
 Surface-mounted, white..... 4007841 086930
 Ceiling installation, white 4007841 086916

PD IR 4360-8 (Presence detector, Ø 8 m)

COM1

Flush-mounted, black 4007841 085117
 Flush-mounted, white 4007841 085124
 Surface-mounted, black..... 4007841 085032
 Surface-mounted, white..... 4007841 085049
 Ceiling installation, black 4007841 085094
 Ceiling installation, white 4007841 085100

DALI2-IPD

Flush-mounted, black 4007841 085759
 Flush-mounted, white 4007841 085766
 Surface-mounted, black..... 4007841 085773
 Surface-mounted, white..... 4007841 085780
 Ceiling installation, white 4007841 085735
 Ceiling installation, black 4007841 085742

KNX

Flush-mounted, black 4007841 086206
 Flush-mounted, white 4007841 086213
 Surface-mounted, black..... 4007841 086169
 Surface-mounted, white..... 4007841 086176
 Ceiling installation, black 4007841 086183
 Ceiling installation, white 4007841 086190

PD IR 4360-24 (Presence detector, Ø 24 m)

COM1

Flush-mounted, black 4007841 085070
 Flush-mounted, white 4007841 085087
 Surface-mounted, black..... 4007841 085018
 Surface-mounted, white..... 4007841 085025
 Ceiling installation, black 4007841 085056
 Ceiling installation, white 4007841 085063

DALI2-IPD

Flush-mounted, black 4007841 085810
 Flush-mounted, white 4007841 085827
 Surface-mounted, black..... 4007841 085834
 Surface-mounted, white..... 4007841 085841
 Ceiling installation, black 4007841 085797
 Ceiling installation, white 4007841 085803

KNX

Flush-mounted, black 4007841 086145
 Flush-mounted, white 4007841 086152
 Surface-mounted, black..... 4007841 086107
 Surface-mounted, white..... 4007841 086114
 Ceiling installation, black 4007841 086121
 Ceiling installation, white 4007841 086138